

シリーズ	オリフィス径	定格	接続	接続口径
2B (二方、1/4回転)	4S (6.35mm)	10 (68 MPa) 11 (75 MPa) 20 (138 MPa)	L (SW) M (AE C&T) P (NPT)	2 (1/8") 4 (1/4") 6 (3/8") 8 (1/2")
2B (二方、1/4回転)	6S (9.52mm)	05 (37 MPa) 10 (69 MPa) 20 (138 MPa)	L (SW) M (AE C&T) P (NPT)	4 (1/4") 6 (3/8") 8 (1/2") 12 (3/4")
2B (二方、1/4回転)	8S (12.7mm)	10 (69 MPa)	M (AE C&T) P (NPT)	12 (3/4") 16 (1")
3B (3位置、1/2回転) 3BD (分岐、1/4回転)	3S (4.77mm)	10 (68 MPa) 11 (75 MPa) 20 (138 MPa)	L (SW) M (AE C&T) H (AE C&T HP) P (NPT)	2 (1/8") 4 (1/4") 6 (3/8") 8 (1/2")
3B (3位置、1/2回転) 3BD (分岐、1/4回転)	6S (9.52mm)	05 (37 MPa) 10 (69 MPa) 20 (138 MPa)	L (SW) M (AE C&T) P (NPT)	4 (1/4") 6 (3/8") 8 (1/2") 12 (3/4")
3B (3位置、1/2回転) 3BD (分岐、1/4回転)	8S (12.7mm)	10 (69 MPa)	M (AE C&T) P (NPT)	12 (3/4") 16 (1")
4B (四方クロス、1/4回転) 4BD (四方切替弁、1/2回転)	6S (9.52mm)	05 (37 MPa) 10 (69 MPa) 20 (138 MPa)	L (SW) M (AE C&T) P (NPT)	4 (1/4") 6 (3/8") 8 (1/2") 12 (3/4")